



## INSTANTANEOUS ELECTRIC STEAM GENERATOR

OUTPUT RANGE

from 16 kW (20 kg/h) to 180 kW (250 kg/h)

WORKING PRESSURE

4.5 bar (on request up to 8.5 bar)

WORKING  
TEMPERATURE

170°C

MODELS

20

30

80

160

250

## DESCRIPTION

Electric steam generator, 99% efficiency <sup>(1)</sup>.

Wattsc is an instantaneous electric steam generator. Designed for a working pressure of 4.5 bar (8.5 bar upon request) and a steam production from 20 up to 250 kg/h (15 – 180 kW). The conformance to the essential safety requirements demanded by the European Pressure Equipment Directive 2014/68/UE (PED) is guaranteed by the CE mark.

### Design features:

The steam generator is composed of one or more pressure vessels having a variable number of electric resistors on board. Such configuration allows the generator to modulate the steam production and the absorbed power.

Installation of the generator is as quick as easy because only 4 connections are necessary: electric power supply, steam supply, drain and water inlet. Water feed can be connected directly to the water mains or to a condensate tank. The control panel manages automatically the steam generator and has an intuitive operational. Because of the vertical design, the WATTSC has a very small footprint.

### Standard equipment: <sup>(2)</sup>

- Steam main valve.
- n. 1 safety valve
- n. 1 reflecting level indicator with cut-off cocks
- n. 1 pressure gauge
- n. 1 safety pressure switch
- n. 1 safety thermostat
- n. 1 water automatic level regulation
- n. 1 feeding group complete with 1 pump
- Valve assembly for feeding circuit, with relevant pipes already fitted
- n. 1 manual bottom blowdown valve
- Control panel board 230/400 V – 3 phases – 50/60 Hz
- Document folder enclosing:
  - Manufacturer's Declaration of Conformity
  - Installation, operation and service manuals
  - Certificates of safety components
  - Control board's electric schemes and related Declaration of Conformity
  - Water characteristics: requirements concerning the quality of water supply, the water in the boiler, frequency and type of sample tests to do.

(1) This value is intended without economizer and may change according working pressure and load conditions.

(2) The quantity and the model may vary according to the configuration.

## TECHNICAL DATA

Model	Steam production	Power input	Standard Working pressure	Optional Working pressure *	Water content
	kg/h	kW	bar	bar	l
<b>20</b>	20	15	4.5	7	16
<b>30</b>	30	22	4.5	7	24
<b>80</b>	83	60	4.5	8.5	55
<b>160</b>	166	120	4.5	8.5	2 x 55
<b>250</b>	249	180	4.5	8.5	3 x 55

\* higher working pressure available on request

## DIMENSIONS

Model	W	L	H	Feed water	Blow down	Steam connection	Condensate return	Empty weight
	mm	mm	mm					kg
<b>20</b>	550	440	980	3/8"	1/2"	1/2"	1/2"	72
<b>30</b>	580	660	730	1/2"	1/2"	1/2"	1/2"	85
<b>80</b>	830	830	570	1/2"	1/2"	1/2"	1/2"	114
<b>160</b>	830	830	1395	1/2"	1/2"	1/2"	1/2"	237
<b>250</b>	1160	950	1670	1/2"	1/2"	1/2"	1/2"	325

